

# MIL/MC3008 Military Battery Charger For MA-4025



- 5 way charger for MA-4025 military batteries. Also available as a 2 output charger.
- 115/230V ac or 24V dc powered for vehicle use.
- Robust construction and easy grip handles for portability
- Vehicle mounting kit includes mounting plate and dc power lead

Charger functions include:

- Pre charge test – to check battery fit to charge
- Normal charge – 14 hour timed charge
- Balance charge – trickle charge to maintain capacity at completion of normal charge.

The MIL/MC3008 is designed for charging most types of military battery, please specify battery type when ordering. The unit is designed and manufactured in the UK giving the user unbeatable product support.

|                               |   |
|-------------------------------|---|
| <b>Dimensions</b>             | <b>290mm x 190mm x 160mm</b>                                |
| <b>Weight</b>                 | <b>6kg</b>  |
| <b>Normal charge current</b>  | <b>440mA</b>  |
| <b>Balance charge current</b> | <b>220mA</b>  |
| <b>Charge termination</b>     | <b>Timed</b>  |
| <b>Number of channels</b>     | <b>5</b>  |
| <b>Output</b>                 | <b>Flying lead</b>  |
| <b>Supply voltage</b>         | <b>110V/230V ac internally switched 50/60Hz, 20V-33V dc</b> |
| <b>Charging temperature</b>   | <b>0°C to +55°C</b>   |
| <b>Storage temperature</b>    | <b>-20°C to +70°C</b>                                       |

**MIL Power Limited.**  
**Celtic House, 44 Ball Moor,**  
**Buckingham. MK18 1RQ**  
**England**

**MIL Power**

**Tel No. +44 (0) 1280 812402**  
**Fax No. +44 (0) 1280 814169**

Email [sales@milpower.co.uk](mailto:sales@milpower.co.uk)  
Web Page. [www.milpower.co.uk](http://www.milpower.co.uk)