

MIL/BA-386/U Battery



- High performance non-rechargeable alkaline battery.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Unit contains safety vented cells
- Cage code: KE507 NSN 6135-99-337-1355

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. The MIL/BA-386U meets the requirements of MIL-B-49030 (Alkaline) with reference to MIL-STD-810 for:

Battery voltage
Mechanical and thermal shock

Capacity test
Vibration

Electrolyte leakage
Insulation resistance

For use in	AN/PRC-77 and AN/PRC-1077 radio sets
Replacement for	BA-3386/U, BA-3186/U, BA-4386/U, BA-5598/U, BA-386/U, BB-586/U
Cell chemistry	Alkaline
Nominal voltage	15.0 Volts
Typical capacity	15Ah
Nominal dimensions	240 x 92 x 54mm
Nominal weight	1.87kg
Connector	Floating type
Case material	Modified ABS
Operating temperature	-20°C to +55°C
Storage temperature	-40°C to +55°C
Disposal	Environmentally safe. Check with local regulations for proper disposal

MIL Power Limited.
Celtic House, 44 Ball Moor,
Buckingham. MK18 1RQ
England

Tel No. +44 (0) 1280 812402
Fax No. +44 (0) 1280 814169

MIL Power

Email sales@milpower.co.uk
 Web Page. www.milpower.co.uk