

# MIL/BB-LA6-69 Battery



- High performance rechargeable sealed lead acid battery using 3 PS1223 cells.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Contains internal PTC protection
- 100% final testing

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-B-11188 with reference to MIL-STD-810 for:

Battery voltage

Capacity test

Electrolyte leakage

Mechanical and thermal shock

Vibration

Insulation resistance

For use in	AN/PRC-77 and AN/PRC-1077,AN/PRC-1099 radio sets
Replacement for	BB-586/U, BB-386/U, BA-386/U, BA-5598/U, TNC386, & TNC386/H
Cell chemistry	Sealed lead acid (lead calcium), 3 PS1223 cells
Nominal voltage	12 Volts
Typical capacity	6.9Ah
Protection	Internal re-settable fuse (PTC)
Nominal dimensions	240 x 92 x 67mm
Nominal weight	2.5kg
Connector	Floating type, 2 phosphor bronze pins fitted
Case material	Modified ABS
Operating temperature	-20°C to +55°C
Storage temperature	-40°C to +55°C

**MIL Power Limited.**  
**Celtic House, 44 Ball Moor,**  
**Buckingham. MK18 1RQ**  
**England**

**Tel No. +44 (0) 1280 812402**

**Fax No. +44 (0) 1280 814169**

**MIL Power**

Email [sales@milpower.co.uk](mailto:sales@milpower.co.uk)

Web Page. [www.milpower.co.uk](http://www.milpower.co.uk)