

MIL/MA-934



- High performance rechargeable nickel cadmium battery.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Unit contains safety vented cells

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-B-49436B with reference to MIL-STD-810 for:

Battery voltage

Capacity test

Electrolyte leakage

Mechanical and thermal shock

Vibration

Insulation resistance

For use in	Racal transceivers
Replacement for	MA-934
Cell chemistry	Nickel Cadmium Rechargeable Battery
Nominal voltage	22.8 Volts
Typical capacity	4.0Ah
Nominal dimensions	344 x 82 x 104mm
Nominal weight	3.77kg
Connector	2 sockets and 2 flat surfaces, nickel plated contacts
Case material	Plastic
Operating temperature	-20°C to +55°C
Storage temperature	-40°C to +55°C
Disposal	Battery must be recycled

MIL Power Limited.
Celtic House, 44 Ball Moor,
Buckingham. MK18 1RQ
England

Tel No. +44 (0) 1280 812402
Fax No. +44 (0) 1280 814169

MIL Power

Email sales@milpower.co.uk
Web Page. www.milpower.co.uk