

MIL/PS-28 Battery



- High performance non-rechargeable alkaline battery.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Unit contains safety vented cells

This battery is engineered and designed for use in a world-wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-B-49030 (Alkaline) with reference to MIL-STD-810 for:

Battery voltage

Capacity test

Electrolyte leakage

Mechanical and thermal shock

Vibration

Insulation resistance

For use in	Elmer RV-3/13P, Thomson TRPP 11/13
Replacement for	PS-28, NSN 6135-13-226-6141
Cell chemistry	Alkaline
Nominal voltage	15.0 Volts
Cells	10 LR12 type
Nominal dimensions	65 x 49 x 108mm
Weight	575 grams max
Connector	2 pin socket
Case material	ABS, olive drab
Operating temperature	-18°C to +45°C
Disposal	Check with local regulations for proper disposal

MIL Power Limited.
Celtic House,
44 Ball Moor,
Buckingham. MK18 1RQ
England

MIL Power

Tel No. +44 (0) 1280 812402
Fax No. +44 (0) 1280 814169

Email sales@milpower.co.uk
Web Page. www.milpower.co.uk