

MIL/R4516 Battery



- High performance rechargeable nickel cadmium battery.
- Durable high impact plastic housing
- High reliability due to all welded construction
- Unit contains safety vented cells

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-PRF-32052 with reference to MIL-STD-810 for:

Battery voltage
Mechanical and thermal shock

Capacity test
Vibration

Electrolyte leakage
Insulation resistance

For use in	PRM-4515 and PRM-4720 radios
Replacement for	MA-4516/A and MA-4516/W
Cell chemistry	Nickel Cadmium
Nominal voltage	9.6Volts
Typical capacity	1000mAh
Typical service life	500 cycles
Nominal dimensions	68 x 75 x 30mm
Nominal weight	260gms
Connector	Twist lock contacts with water tight O ring around centre contact
Case material	Black high impact engineering plastic
Operating temperature	-20°C to +55°C
Storage temperature	-40°C to +55°C
Shelf life	Five (5) Years under controlled storage. (+ 4°C, 50% R.H)
Disposal	Battery must be recycled

MIL Power Limited.
Celtic House, 44 Ball Moor,
Buckingham. MK18 1RQ
England

Tel No. +44 (0) 1280 812402
Fax No. +44 (0) 1280 814169

MIL Power

Email sales@milpower.co.uk
Web Page. www.milpower.co.uk