

MIL/TNC-624 Battery



- High performance rechargeable nickel cadmium battery.
- Durable high impact plastic housing
- High reliability due to all welded construction
- Unit contains safety vented cells

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-PRF-32052 with reference to MIL-STD-810 for:

Battery voltage

Capacity test

Electrolyte leakage

Mechanical and thermal shock

Vibration

Insulation resistance

For use in	PRC-624
Replacement for	TNC-624
Cell chemistry	Nickel Cadmium
Nominal voltage	12Volts
Typical capacity	1100mAh
Typical service life	500 cycles
Dimensions	77 x 38 x 77.5mm
Weight	450 gms
Case material	High impact engineering plastic
Operating temperature	-25°C to +55°C
Storage temperature	-25°C to +65°C
Shelf life	Five (5) Years under controlled storage. (+ 4°C, 50% R.H)
Disposal	Battery must be recycled

MIL Power Limited.
Celtic House, 44 Ball Moor,
Buckingham. MK18 1RQ
England

Tel No. +44 (0) 1280 812402

Fax No. +44 (0) 1280 814169

MIL Power

Email sales@milpower.co.uk

Web Page. www.milpower.co.uk