

MAI-150745 Lithium Ion Battery

- High Power rechargeable Lithium Ion battery with instantaneous start up, specifically designed to support ALL the AN/PRC-112 family.
- For training purposes only.
- Durable high impact plastic housing.
- High capacity, performance verified, hermetically sealed, Lithium Ion cells.
- Protection against short circuit and improper charge.
- State of Charge Indicator using 5 segment LCD.
- Watertight upon installation.
- Gold plated contacts.
- Charge using MAI-150750 charger



For use in

AN/PRC-112G, Hook 2 G and all PRC-112 survival radios, KY-913, and GPS-112 Program Loader

Rechargeable training replacement for

1794AS0953-/U, 1794AS0953A/U, 1794AS0953B/U, 1794AS0953C/U, 1794AS0953E/U, BA-5312/U, BA-5112/U

Cell chemistry

Lithium Ion

Nominal voltage

12.0Volts

Typical capacity

2.6Ah

Max discharge current

3.0Ah continuous from -20°C to +60°C

Nominal dimensions

78 x 57 x 39 mm, 3.07" x 2.24" x 1.54"

Weight

272 grams, 0.6lbs

Connector

2 gold plated contacts

Case material

High impact engineering plastic

Case colour

Tan

Operating temperature

-20°C to +60°C

Storage temperature

-55°C to +71°C

MIL Power Limited
Celtic House, 44 Ball Moor
Buckingham, MK18 1RQ
United Kingdom

Tel: +44 1280 812402
Fax: +44 1280 814169
Email: sales@milpower.co.uk
www.milpower.co.uk
www.maifl.com

