

MIL/MC3008 Military Battery Charger for BB-590/U



- 5 way charger for military BB-590/U batteries.
- 115/230V ac, or 24V dc supply for vehicle use
- Robust construction and easy grip handles for portability
- Vehicle mounting kit includes mounting plate and dc power lead

Charger functions include:

- Pre charge test – to check battery fit to charge
- Normal charge – 14 hour timed charge - safe on a charged battery, no need to discharge before charging.
- Balance charge – trickle charge to maintain capacity at completion of normal charge.

The progress of the charge cycle is shown by the front panel indicators. Green for charging, flashing green for charge complete and flashing red for a defective battery.

Dimensions	290mm x 190mm x 160mm
Weight	6kg
Normal charge current	240mA
Balance charge current	120mA
Charge termination	Timed
Number of channels	5
Output	Flying lead
Output power	50 Watts
Supply voltage	110V/230V ac internally switched 50/60Hz, 20V-30V dc
Charging temperature	0°C to +50°C
Storage temperature	-20°C to +70°C

MIL Power Limited.
Celtic House, 44 Ball Moor,
Buckingham. MK18 1RQ
England

Tel No. +44 (0) 1280 812402
Fax No. +44 (0) 1280 814169

MIL Power

Email sales@milpower.co.uk
Web Page. www.milpower.co.uk