

# MIL/BA-5374/U Battery



- High performance non-rechargeable Lithium Manganese Dioxide battery.
- Durable high impact plastic tube
- High reliability due to all welded construction

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-B- 49471 with reference to MIL-STD-810 for:

Battery voltage	Capacity test	Electrolyte leakage
Mechanical and thermal shock	Vibration	Insulation resistance

For use in	Life preserver, CO <sub>2</sub> inflation, mine sweeping equipment, distress marker light SDU-5/E, ACR-4F, ACR-4G
Replacement for	BA-1574/U, BA-5374/U
Cell chemistry	Lithium Manganese Dioxide
Nominal voltage	6.0 Volts
Nominal Capacity	1400mAh
Nominal dimensions	Diameter 17.0mm, Height 60mm
Nominal weight	57gms
Connector	Positive: screw, negative: flat surface
Case material	Black plastic tube
Operating temperature	-20°C to +55°C
Storage temperature	-20°C to +55°C
Disposal	Environmentally safe. Check with local regulations for proper disposal

**MIL Power Limited.**  
**Celtic House, 44 Ball Moor,**  
**Buckingham. MK18 1RQ**  
**England**

**Tel No. +44 (0) 1280 812402**  
**Fax No. +44 (0) 1280 814169**

**MIL Power**

Email [sales@milpower.co.uk](mailto:sales@milpower.co.uk)  
 Web Page. [www.milpower.co.uk](http://www.milpower.co.uk)