

MIL/BB-4600 Battery



- High performance rechargeable nickel cadmium battery.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Unit contains safety vented cells

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-B-49436B with reference to MIL-STD-810 for:

Battery voltage

Capacity test

Electrolyte leakage

Mechanical and thermal shock

Vibration

Insulation resistance

| | |
|-----------------------|---------------------------------------------------|
| For use in | PRC-4620 radio set and TC-600 remote control unit |
| Replacement for | BB-4600 |
| Cell chemistry | Nickel Cadmium |
| Nominal voltage | 14.4 Volts |
| Typical capacity | 4.0Ah |
| Nominal dimensions | 234 x 70 x 64mm |
| Nominal weight | 1.85kg |
| Connector | Floating type |
| Case material | Modified ABS |
| Operating temperature | -20°C to +55°C |
| Storage temperature | -30°C to +55°C |
| Disposal | Battery must be recycled |

MIL Power Limited.
Celtic House,
44 Ball Moor,
Buckingham. MK18 1RQ
England

MIL Power

Tel No. +44 (0) 1280 812402

Fax No. +44 (0) 1280 814169

Email sales@milpower.co.uk

Web Page. www.milpower.co.uk