

MIL/BB-590/U Battery



- Cage Code: KE507 NSN: 6140-01-063-3918
- High performance rechargeable nickel cadmium battery.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Unit contains safety vented cells

This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed US MIL-SPEC and ISO9000 methods and procedures. This battery meets the requirements of MIL-PRF-32052 with reference to MIL-STD-810 for:

Battery voltage	Capacity test	Electrolyte leakage
Mechanical and thermal shock	Vibration	Insulation resistance

For use in	PRC-104, PRC-119, PRC-138, KY-57 and other equipment
Replacement for	BB-590/U, BA-3590/U, BA-5590/U, BB-490/U, BB-390A/U
Cell chemistry	Rechargeable, Nickel Cadmium Battery
Nominal voltage	24 Volts or two 12V sections depending on connection
Typical capacity	2.4Ah @ 24V, 4.8Ah @ 12V
Nominal dimensions	112 x 63 x 125 mm
Nominal weight	1.35kg
Venting	Battery has pressure release valve
Case material	Modified ABS
Operating temperature	-20°C to +55°C

MIL Power Limited.
Celtic House,
44 Ball Moor,
Buckingham. MK18 1RQ
England

MIL Power

Tel No. +44 (0) 1280 812402
 Fax No. +44 (0) 1280 814169

Email sales@milpower.co.uk
 Web Page. www.milpower.co.uk